

# CLARIUS®

## LED Illuminators

INFRA-RED

### Extra Large IR LED Illuminator

The Clarius® Plus range of high performance Infra-Red LED illuminators are designed to provide class leading performance, long life and ultra low maintenance.

Incorporating the latest surface mount Dual Core® LED's with enhanced optical output and outstanding reliability, they deliver excellent night-time images.

Each unit is fitted with integrated control circuitry to carefully control LED output, delivering consistent illumination and projected working life in excess of 10 years.

The Clarius® Plus range of illuminators includes a new interchangeable lens diffuser system; which allows the user to quickly and easily alter the angle of illumination. Elliptical beam profiles allow more light to be delivered where it is needed, allowing both longer distances and minimising light wastage. The system also helps to prevent overexposure of foreground objects.

As standard the illuminator includes interchangeable lensing to deliver 10° circular, 30°, 60° and 95° elliptical beam profiles.

Installation is quick and easy, requiring only 12-32V DC / 24V AC +/- 10%.

#### PRODUCT CODES

**IX-8** Extra Large Clarius PLUS Infra-Red Illuminator 850nm

**IX-9** Extra Large Clarius PLUS Infra-Red Illuminator 940nm

#### Recommended PSU

ALT-60-24



#### Interchangeable Diffuser Lens



#### FEATURES

Latest Dual Core® SMT LED technology

Distances up to 262m (859')

Angle 10°, 30°, 60° & 95°

Elliptical beam profiles

850nm or 940nm wavelengths

Low power consumption (52W)

Long life

5 year warranty

IP66 weather proof rating

Built-in photocell IR on/off

Photocell following contact

Telemetry input for remote switching

12-32V DC / 24V AC +/- 10%

CleanLITE® self cleaning lens coating technology


Pressure equalisation vent

High quality anodised aluminium heatsink

# SPECIFICATIONS

Product Code	Wavelength	Angle	Distance		FOV	
IX-8	850nm	10° - Circular	262m	859'	46m	150'
		30° - Elliptical	131m	429'	70m	230'
		60° - Elliptical	83m	273'	96m	316'
		95° - Elliptical	42m	137'	91m	298'
IX-9	940nm	10° - Circular	161m	527'	28m	92'
		30° - Elliptical	91m	299'	49m	160'
		60° - Elliptical	56m	184'	65m	212'
		95° - Elliptical	28m	92'	61m	201'

Other angles available on request.



## GENERAL

<b>ELECTRONICS</b>	High efficiency surface mount high power dual core® with advanced current limited integral control circuitry
<b>CONSTRUCTION</b>	Robust high quality aluminium extrusion
<b>FRONT WINDOW</b>	Polycarbonate high transmission protective (vandal proof) ir filter with CleanLITE® technology
<b>FINISH</b>	Black anodised
<b>POWER CABLE</b>	3m (9ft) including photocell following contact & remote telemetry input
<b>PRESSURE EQUALISATION VENT</b>	Prevents thermal expansion & pressure cycling
<b>PHOTOCELL</b>	Adjustable 20 -70 Lux
<b>ILLUMINATION</b>	Adjustable 10% - 100%
<b>OPERATING TEMPERATURE</b>	-50° to 50°C (-58° to 122°F)
<b>WEIGHT</b>	1.75Kg (3.9lbs)
<b>MOUNT</b>	Powder coated stainless steel wall mount
<b>DIMENSIONS</b>	213 x 110 x 78mm (8.39" x 4.33" x 3.07")

## ELECTRICAL

<b>INPUT VOLTAGE</b>	12-32V DC or 24V AC +/-10%
<b>INPUT CURRENT</b>	2.2A at 24V AC
<b>CONSUMPTION</b>	52W

## WAVELENGTH

<b>STANDARD</b>	850nm (Semi Covert). Faint Red Glow Only
<b>OPTIONAL</b>	940nm (Covert). Minimal visible glow

## CERTIFICATIONS

<b>WEEE</b>	Waste electrical & electronic equipment european directive 202/96/EC	
<b>RoHS</b>	Restriction of hazardous substance european directive 202/95/EC	
<b>CE-EMC</b>	EN 61547 EN 55015 EN 62493 EN 50130-4 EN61000	(Lighting-Immunity) (Lighting-Emission) (Lighting-EMF) (Alarm-EMC) FCC Part 15. 107 15. 108 Class B
<b>CE-LVD</b>	EN 60598-1 EN 60598-2-1 EN 62368-1 / EN 60950-22	(Luminaires-General) (Luminaires)
<b>SAFETY</b>	EN 62471 EN60598:2004 EN60825-1	(LED safety) Electrical Safety Laser Eye Safety
<b>IP</b>	IP66 In Accordance With EN60529:1992	
<b>ENVIRONMENTAL</b>	IEC/EN 60529 IEC/EN 62262 EN 50130-5 N2580, EN 50581	IP66 IK09 (Alarm-environmental) (RoHS), REACH
<b>USA</b>	cULus FCC	UL 2108 UL 8750 Class B
<b>AUS</b>	RCM (AS/NZS CISPR 22 Class B)	